

CEL633A Environmental Sound Level Meter



Features

- Data Logging with Time History Noise Profile stores
- Voice Notes and Audio Recording
- Automatic Timers
- Measures Leq, Lavg, Min, Max, Ln, etc. Simultaneously
- Range: 20 to 140 dB(A)
- Data Markers and Back Erase

Applications

- Environmental Noise Surveys
- Occupational Noise Measurement

Overview

The CEL633A Sound Level Meter is for measuring environmental noise in communities and around the perimeter of industrial sites.

The CEL633A sound level meter is available as either Type 1 or Type 2 - the most common for environmental noise measurement and more accurate being Type 1. This meter also has everything needed for occupational noise measurement in line with the OSHA, MSHA, ACGIH and EU regulations, making it ideal for anybody involved in both environmental (outside the factory) and occupational (inside the factory) noise.

If the meter is to be left unattended in poor weather conditions then the **Outdoor Kit** should be used to offer protection against the elements. The Outdoor Kit also includes a rechargeable battery pack for longer term monitoring.

Standards

- ANSI S1.4 and ANSI S1.43 to Type 1 or Type 2
- IEC 61672 Class 1 or Class 2
- IEC60851 and IEC 60804 Type 1 or Type 2

Average Sound Level and Statistical Parameters

The CEL633 has a very wide span, covering 20 to 140dB in a single range. This is particularly important when monitoring in an environment with generally low noise levels and occasionally high ones - for example when cars pass. The most useful parameter when measuring environmental and community noise is the Leq, the average sound level. The meter measures the periodic Leq and also includes five Ln values for statistical analysis of the noise.

Data Logging and Software

The CEL633A comes complete with data logging capability with measurements stored in the meter's large internal memory.

CasellaDrive

When connected to a Windows computer using the free CasellaDrive software, the meter acts like a memory stick (shows as a removable drive) so the measurements can be loaded into a spreadsheet or moved to your hard drive for long term storage. There is no need to buy special software.

Insight

Due to the large amount of data and the potential complexity of the measurements, we would recommend the use of the Insight software. It simplifies the process of downloading the measurements and stores them in a database, managed by person, place or process criteria. The Insight software is included with the sound level meter.

CEL633A Environmental Sound Level Meter

Specifications

Specifications

The CEL633A data logging Integrating Sound Level Meter is available as either Type 1 (CEL633A1) or Type 2 (CEL633A2) as defined by the international sound level meter standards.

Measured Parameters

| | |
|--|--------------------------------|
| Frequency weightings | A, C and Z (simultaneous) |
| Time weightings | Fast, Slow and Impulse |
| Amplitude weightings | Q3, Q4 and Q5 |
| Thresholds | 70 to 90 dB (applies to Lavg) |
| Sound Level | LXY, LXYMax, LXYMin, LC-LA |
| Integrated Peak | LXeq, Lavg, LAE |
| Takt Max | LXPeak |
| Statistical | LTM3, LTM5, LXleq |
| Time History Level 1 | 5 x Ln values |
| Time History Level 2 | Periods of 1 minute to 1 hour |
| Time History Level 2 | Periods of 1 second to 30 mins |
| Where X is frequency weighting A, C or Z and Y is time weighting Fast, Slow or Impulse | |

Sound Level Meter Standards

- ANSI S1.4 and ANSI S1.43 Type 1 or Type 2
- IEC 60651 and IEC 60804 Type 1 or Type 2
- IEC 61672 Class 1 or Class 2

Using a meter that meets these standards is essential for repeatable results and especially for any measurements that will be used for legal purposes.

| | |
|-------------------|--|
| Measurement range | 20 to 140 dB (single range), 143 dB Peak |
| Display | 320 x 240 pixel color TFT |
| Output to PC | USB Mini B |
| Batteries | 3 x AA Alkaline (15 hours with backlight off) |
| External Power | 9 to 14V DC at 250mA (2.1mm connector) |
| Dimensions | 72 x 229 x 31mm, 295g 2.8" x 9.0" x 1.2". 10.4oz |
| Memory | 2GB >1 year when logging set to 1 second |
| Timers | Duration 1s to 24h On/Off Timers: 6 sets with selectable times and repeat function. |
| Audio Recording | 8kHz sampling, 60 hours recording 24kHz sampling, 10 hours recording |

Head Office

NoiseMeters Ltd
7 Jayes Park
Ockley
Surrey
RH5 5RR

Telephone **0845 680 0312**
Fax **0845 680 0316**

Email: **info@noisemeters.co.uk**
Support: **support@noisemeters.co.uk**

Web Sites

Main site:
<https://www.noisemeters.co.uk>

Product shortcut:
<https://www.noisemeters.co.uk/p/cel633a1/>

Tech Support:
<https://support.noisemeters.com>