

## Octave Band Combination Kit - Noise at Work



### Features

- One or more doseBadge Pro noise dosimeters
- Hand held CR162C Optimus Red octave band sound level meter
- Protective Peli Case
- Full survey using hand-held meter and/or dosimeters
- All calibrated equipment

### Applications

- UK and EU Noise at work regulations
- Assessing mobile and stationary workers
- Full noise at work survey using meter or dosimeter
- Hearing protection assessment with octave band filters

### Overview

The Octave Band Combination Kit is ideal for very high noise level environments. Both sound level meter and noise dosimeters have real-time octave band filters for a more detailed description of the noise.

The hand-held meter and the dosimeters both make all the measurements needed by the noise at work regulations, so either can be used to make a full assessment and noise reports. You have the option to choose which method to use: hand held or noise dosimetry.

### Octave Band Filters

The octave band filter measurements can be used to analyse machinery noise in more detail. For noise at work measurement the most common use for octave bands is for detailed selection of hearing protectors. This can be carried out in the NoiseTools software that is included.

### Kit Contents

The Octave Band Combination Kit includes the following:

- doseBadge Pro noise dosimeter(s)
- doseBadge Charger and USB Dock
- CR162C Logging, Octave Band Sound Level Meter
- CR514 Sound Level Calibrator
- NoiseTools Software
- Strong, weatherproof carry case
- Calibration certificates for meter, dosimeters and calibrator

This kit includes everything needed for a full noise at work assessment in line with the UK and EU guidelines, including areas with very high noise levels that benefit from an octave band analysis.

## Octave Band Combination Kit - Noise at Work

### Specifications

#### doseBadge Pro Noise Dosimeter Specifications

Standards	IEC 61252 Personal Sound Exposure Meters ANSI S1.25 Personal Noise Dosimeters
Range	RMS: 60 to 140 dB(A), Peak: 80 to 143 dB
Octave Bands Parameters	Real-time, 63Hz to 8kHz Date/time, Leq, Lavg, TWA, LEP,d, Lex,8, %Dose, Peak
Communication	Bluetooth to mobile app, USB to computer
Programmable	Exchange rate, criterion level & time, Threshold, Time Weighting
Logging	1 second or 1 minute time history (user selectable)
Dimensions	66 x 43 x 53mm, 2.54" x 1.69" x 2.01"

For more detailed specifications please visit the doseBadge Pro Noise Dosimeter page.

#### CR162C Octave Band Meter Specifications

Standards	IEC 61672 Class 2 ANSI S1.4 Type 2
Range	20 to 140 dB
Freq.	A, C and Z
Weighting	Fast, Slow and Impulse
Time	
Weighting	
Time History	10ms, 62.5ms, 100ms, 125ms, 250ms, 1/2 sec, 1 sec or 2 sec
Filters	10 octave bands from 31.5Hz to 16kHz
Memory	4 GB
Power	4 x AA batteries

For more detailed specifications please visit the CR162C Sound Level Meter page.

---

#### Head Office

NoiseMeters Ltd  
7 Jayes Park  
Ockley  
Surrey  
RH5 5RR

Telephone **0845 680 0312**  
Fax **0845 680 0316**

Email: **info@noisemeters.co.uk**  
Support: **support@noisemeters.co.uk**

#### Web Sites

Main site:  
<https://www.noisemeters.co.uk>

Product shortcut:  
<https://www.noisemeters.co.uk/p/cmb162c/1/>

Tech Support:  
<https://support.noisemeters.com>