

doseBadge Pro Noise Dosimeter



(c) NoiseMeters

Features

- Strong anti-tamper design
- Data logging with schedule timers
- Multiple channels for all regulations
- Real-time octave band filters
- Bluetooth and mobile app
- Fast charge time

Applications

- Noise at work assessments
- Occupational noise surveys
- Noise exposure measurements
- Factories and industrial sites
- Hearing protection assessment

doseBadge Professional Overview

The doseBadge Professional is a high specification noise dosimeter for monitoring a worker's exposure to high noise levels in the workplace. It mounts on a worker's shoulder in order to measure the total noise exposure throughout the working day or shift. This Professional version makes all the measurements of the lower cost Industrial doseBadge but adds a number of useful features for a deeper analysis of the sound levels, better measurement control and more detailed reporting.

Noise Regulations

The doseBadge Pro can be configured to comply with any occupational noise regulations, standards or guidelines. As it has four independent channels or integrators it can be configured to meet multiple regulations at the same time.

For the UK and elsewhere in Europe it meets the requirements of EU Physical Agents (Noise) Directive 2003/10/EC and the HSE's guidelines for assessing noise at work. As the doseBadge's four integrators are configurable, it can be set to meet other regulations should you need to use it outside the UK.

doseBadge Industrial or doseBadge Professional

The doseBadge Industrial is a slightly lower cost noise dosimeter that offers the functions required by the noise at work regulations, but of course doesn't have many of the advanced features offered by the Professional.

The following features are only available in the Professional version:

- Timers to start measurements automatically
- Real-time octave band filters
- Easier and better selection of hearing protection
- Bluetooth link to mobile phone app (see **Software** tab)
- 4 independent channels for combined regulations
- Docking station for charging and USB download
- Internal shock sensor to detect impact and tampering

doseBadge Pro Noise Dosimeter

Specifications

doseBadge Pro Specifications

Standards	IEC 61252:1993 +AMD1:2000 Personal Sound Exposure Meters IEC 61252 Ed 1.1 (2002-03) Personal Sound Exposure Meters ANSI S1.25:1991 (R2017) Personal Noise Dosimeters IEC 61260-1:2014 Class 2 (Octave Bands from 63Hz to 8kHz) ANSI S1.11-2014 Class 2 (Octave Bands from 63Hz to 8kHz)	Integrator Options	Channel name - Preset or user defined Exchange rate - 3, 4 or 5 dB Criterion Level - 80 dB to 100 dB in 1 dB steps Criterion Time - 1 hr to 24 hrs in 1hr steps Threshold Level - None, 70 dB to 100 dB n 1dB steps Time Weighting - Fast, Slow or None Frequency Weighting - A, C or Z Upper Limit Level - 70 dB to 140 dB in 1 dB steps Upper Limit Time Weighting - None, Fast or Slow Upper Limit Freq. Weighting - A,C, or Z SPL Max Time Weighting - Fast or Slow SPL Max Freq Weighting - A,C or Z LED Threshold Trigger - User selectable channel with user selectable % Dose trigger levels (75% to 100% in 5% steps) Frequency weighting - A,C or Z (2 channels)
Range	RMS Range - 60 dB(A) to 140 dB(A) Peak Range - 80 dB(C) to 143 dB(C) Octave Bands - 70 dB(A) to 140 dB(A)	Peak Options	Automatic detection of external acoustic calibration User configurable calibration level (typically 114dB or 94dB)
Functions	4 Simultaneous Independent Integrator Channels 2 Simultaneous Independent Peak Channels 1:1 Octave Bands (63Hz to 8kHz)	Calibration	1 second or 1-minute time history data (user selectable)
Parameters	Measurement duration, Start time & date, Instrument serial number & name Calibration information (field & factory calibration), Overload & Tamper sensor detection	Data Logging	Up to 80 hours of Time History Data for each channel including 1:1 Octave Bands
Integrator Params	Average Integrated Sound Level (Leq/Lavg), Time Weighted Average (LEP,d/LEX,8/TWA) Sound Exposure & Estimated Sound Exposure, % Dose & Estimated % Dose, ULT Duration SPL Max Level & Time, SPL Min Level	Memory	Up to 40 individual measurements Maximum duration of any single measurement: 24 hours
Peak Channel	Overall LPeak level for each channel (Up to 2 channels)	Dimensions	66 mm x 43 mm x 53 mm (excluding clips) 2.53" x 1.69" x 2.01" (excluding clips)
Octave Bands	Overall unweighted Leq for each octave band (63Hz to 8kHz)		85 g/2.9 oz
Communication	Bluetooth Wireless communication to the RC120A Wand Bluetooth Wireless communication to the dBLink App (Android & iOS) USB download to NoiseTools via the doseBadge Dock		

Head Office

NoiseMeters Ltd
7 Jayes Park
Ockley
Surrey
RH5 5RR

Telephone **0845 680 0312**
Fax **0845 680 0316**

Email: info@noisemeters.co.uk
Support: support@noisemeters.co.uk

Web Sites

Main site:
<https://www.noisemeters.co.uk>

Product shortcut:
<https://www.noisemeters.co.uk/p/ck120/1/>

Tech Support:
<https://support.noisemeters.com>