

## LiveNoise Terminal with Low Cost Microphone



### Features

- Monitors and Stores Sound Levels
- Network Connection (WiFi or Ethernet)
- Easily Wall Mounted
- Accurate Sound Level Indicator

### Applications

- Office Noise
- High Noise Level Alarm
- Steam Leak Monitoring

### Low Cost Noise Monitor

This LiveNoise monitor is fitted with a low cost microphone. While it gives an accurate measurement of the relative sound level, it is not intended for applications that need a monitor meeting standards such as IEC 61672 and ANSI S1.4. Please see our other noise monitors for these applications.


The LNT-M is ideal for monitoring long term relative noise levels and warning when levels go unexpectedly high. A typical application would be monitoring for high pressure steam leaks in an industrial environment.

It is also ideal for monitoring the noise levels in open plan offices. A mixed system including this low cost version along with the LNT-320 or LNT-EAR noise monitors can be used to monitor larger areas with additional accuracy at key locations.

The noise monitor can communicate continuously with the LiveNoise Supervisor software to provide real-time noise levels, long-term stored noise measurements and high-noise alarms. The LiveNoise Reporter software can generate long term reports.

Alternatively, you can use the Web Reporter for online noise reports.

An HDMI monitor can be connected to provide a large display of sound levels. The display can even be an old VGA monitor that you have hanging around, but you will need an HDMI to VGA adapter.



## LiveNoise Terminal with Low Cost Microphone

### Specifications

#### Technical Specifications

|                     |   |
|---------------------|---|
| Measuring Range     | 50 to 120 dB                                    |
| Frequency Weighting | "A"   |
| Noise Measurements  | Leq, Fast Sound Level                           |
| USB Port            | For USB memory stick configuration and keyboard |
| Ethernet Port       | RJ45 socket                                     |
| Video Output        | HDMI  |
| Internal Memory     | 16 GB for up to 5 years storage                 |
| Dimensions          | 70 x 88 x 29 mm, 2.8" x 3.5" x 1.2"             |
| Power               | 5 VDC, max 12W (power adapter included)         |

#### LiveNoise LNT-M Dimensions

---

#### Head Office

NoiseMeters Ltd  
7 Jayes Park  
Ockley  
Surrey  
RH5 5RR

Telephone **0845 680 0312**  
Fax **0845 680 0316**

Email: **info@noisemeters.co.uk**  
Support: **support@noisemeters.co.uk**

#### Web Sites

Main site:  
<https://www.noisemeters.co.uk>

Product shortcut:  
<https://www.noisemeters.co.uk/product/livenoise1/lnt-m/>

Tech Support:  
<https://support.noisemeters.com>